



Portable

PRAMAC portable division meets the needs of both professional and amateur users, offering a wide product range: from electric generator sets to water pumps, from pressure washers to welder generators. Quality, efficiency and high product standards are achieved through the use of modern design and manufacturing techniques, exceeding international regulations for noise and environmental pollution.



W Series

Welder generators specifically designed for small repairs, or for more advanced applications. Up to 220A you can use rutile, basic or cellulosic electrode up to 5mm diameter.



Optional




PETROL

PROPERTIES ADVANTAGES



Different types of plugs available for welders



Fully equipped control panel for welder and genset

OPTIONALS



Transportation kit with fixed handles



Transportation kit with height-adjustable folding handles



Complete welding kit: mask, gloves, brush, box for electrodes, light glasses 90x110 mm (5x), dark glass, welding wire 35 mm² - 5m- with plug dia. 13mm, ground wire 35 mm² - 5m- with plug dia. 13mm

W SERIES PETROL		
WELDER GENERATOR		W 220
WELDER PARAMETERS		
WELDING CURRENT	A	40 / 220
MIN/MAX WELDING VOLTAGE	V	21,6 / 28,8
WELDING SERVICE at 60%	A	170
MAX DIAMETER OF ELECTRODE		
RUTILE	mm	5
BASIC	mm	5
CELLULOSE	mm	5
POWER GENERATOR		
VOLTAGE	V	400 / 230
FREQUENCY	Hz	50
POWER THREE PHASE		
STAND BY POWER LTP	kW / kVA	5,5 / 6,1
CONTINUOUS POWER COP	kVA	5,2
POWER SINGLE PHASE		
STAND BY POWER LTP	kW / kVA	2,4 / 2,7
CONTINUOUS POWER COP	kVA	2,3
ENGINE		
BRAND		Honda
MODEL		GX390
FUEL		Petrol
DISPLACEMENT	cc	389
SPEED	rpm	3000
COOLING SYSTEM		Air
STARTING SYSTEM		Recoil
CONSUMPTION		
FUEL CONSUMPTION at 75% of load	L/h	2,2
FUEL TANK CAPACITY	L	6,1
FUEL TANK MATERIAL		Metal
RUNNING TIME at 75% of load	h	2,8
NOISE EMISSION		
NOISE PRESSURE LEVEL at 7 mt	db(A)	72
GUARANTEED SOUND POWER LEVEL	LWA db(A)	97
DIMENSION AND WEIGHT		
LENGTH	mm	875
WIDTH	mm	620
HEIGHT	mm	600
WEIGHT (DRY)	kg	80
STANDARD EQUIPMENTS**		
SOCKETS		2 x welding socket
		1 x 230V Schuko 16A
		1 x 230V CEE 16A
		1 x 400V CEE 16A
ALTERNATOR AND SOCKET PROTECTION		
ALTERNATOR PROTECTION	IP	23
SOCKET PROTECTION	IP	44
OPTIONALS		
WELDING KIT		0
TRANSPORTATION KIT With fixed handles		0
TRANSPORTATION KIT With folding handles		0

**= Other configurations and detailed specifications are available on www.pramac.com - 0 = Accessory available