

Worm pump SP 11 LMR

Convenient plastering machine for pre-mixed mortar and site-mixes

The all new SP 11 LMR is a compact, lightweight worm pump specially designed to achieve outstanding performance, simple operation and easy servicing. The delivery rate can be infinitely adjusted to max. 60 l/min*. The machine can pump deliver up to horizontal distances of 120 m** or heights of 60 m**.

SP 11 LMR models are suitable for use with site-mixes or pre-mixed interior and external plasters supplied in bags, monocoat, fire-proofing mortar, base coat plaster, lightweight masonry mortar, ornamental plaster, and filling/grouting work.

Part no. 111 622.010



Technical data	SP 11 LMR
Version	Lifting mixer
Pump type	2L6
Delivery pressure	25 bar
Theor. delivery rate*	5-60 l/min
Delivery distance**	horizontal distances of 120 m, heights of 60 m
Compressor	2-cylinder compressor, 400 l/min, 7 bar
Trap mixer	180 l
Conveyor hopper	220 l
Engine	3-cylinder Kubota, 16.3 kW at 2,600 rpm
Chassis	without brakes, approved for road use
Weight	750 kg
Length x width x height	3.540 x 1.420 x 1.150 mm
Filling height	880 mm
Maximum grain size	6 mm

* The delivery rate is theoretical and depends on the pump model.
Depending on the pump used, the delivery rate may be higher or lower.

**The data is based on experience and is dependent on the materials used.



Powerful worm pump 2L6 with pressure connection piece to attach hoses.



The maximum motor speed of just 2,600 rpm and good sound insulation make the SP 11 more quiet than other machines.



All SP 11 functions can be controlled from the operating panel.
The machine conforms with CE standards.

Supplementary equipment	SP 11 LMR
Standard colour paintwork	●
Special colour paintwork (hood)	○
High-pressure cleaner	●
Car coupling	●
Truck coupling	○
Mechanical water metering	●
Support wheel	○
Vibrating screen	○
Working lights	○
Key:	- not available ○ optional ● standard feature