

Electrical Shears

CEL 30 / 30M / 35 / 45



- Cast-iron Monoblock chassis
- Easy and safe operating by foot pedal or lever



Easy and quick safety device.

Impossible to operate by its pedal or lever when the protector is up, complying then with CE regulations.



Longer Life and Top Performance

- The inner mechanisms (gears, bearings, shafts, etc), which are affording high efforts and usage, are thermically treated. This implies longer life and top performance.
- Interchangeable rectangular knives with 4 cutting sides.
- Higher efficiency in small and medium sized diameters because of its larger "throat" and cutting knives.
- Group of gears are bath in oil.
- Easily transportable thanks to its hook and handle.



Technical specifications

Technical specifications		CEL 30	CEL 30M	CEL 35	CEL 45
R=N/mm.2	R=450 Smooth - N° BARS 1 - 2 - 3	30 - 20 -16	30 - 20 - 16	35 - 25 - 16	45 - 34 - 24
	R=650 Rebar - N° BARS 1 - 2 - 3	25 - 20 - 16	25 - 20 - 16	32 - 25 - 16	40 - 32 - 25
Turns / minute		110	110	100	50
Motor power (Kw)		1,5	1,5	2,2	3
Motor phase (S/T)		Three Phase	Single Phase	Three Phase	Single Phase
Net weight (Kg)		247	247	342	666
Dimensions (LxWxH, mm)		831x544x728	831x544x728	933x631x689	1147x640x915