

SAEZ

CRANES



S52 4T



S52 4T

DIN/FEM 


UNE 58-101-92 FEM 1001-87
According to EC 98/37 instruction

Windzone A-B / DIN 15019


Viento max. fuerza de servicio 150km/h
Maximun wind speed out of service 150 km/h
Maximale windstärke, ohne Betrieb 150 km/h
Vent maximum, hors service 150 km/h
Vento max, fuori di servizio 150 km/h




A



B



C



D

Bloque de contrapeso
Counterweight blocks
Gegengewichtsblöcke
Bloc de contrepoid
Blocco di contrappeso

	52 m			50 m			46,5 m			41 m		
	A	B	C	A	B	C	A	B	C	A	B	C
	5	-	-	5	-	-	5	-	-	4	-	1
	11500 Kg			11500 Kg			11500 Kg			10050 Kg		

	35 m			30 m			23,6 m		
	A	B	C	A	B	C	A	B	C
	3	1	-	3	-	-	2	-	-
	8300 Kg			6900 Kg			4600 Kg		

	25 m	50 m	100 m
15 Hp (11,5 KW) 3V	4 x 16 mm ²	4 x 16 mm ²	4 x 25 mm ²
25 Hp (18,5 KW) 3V	4 x 25 mm ²	4 x 25 mm ²	4 x 25 mm ²
25 Hp (18,5 KW) INV	4 x 25 mm ²	4 x 25 mm ²	4 x 25 mm ²

 CEI 38 IEC 38	400 V 50 Hz	* 380 V 60 Hz	* 25 Hp (18,5 Kw) 31 KW / 120 kVA
			15 Hp (11,5 Kw) 3V 24KW / 90 kVA

Windzone A-B / DIN 15019


Mástil / Reacciones

Masts / Reactions

Maste / Eckdrücke

Mat / Réactions

Torre / Reazioni



D: TORRE S/TL 50-52 1.20 M39/M39 8/8
E: TORRE TL 55 1.20 M39/M39 8/8
J: CAMPANA S17 10m 1.2/1.7 M39/M45 8/8
K: TORRE S17 1.70 M45 8/8
L: TORRE S17 1.70 M45 16/8
M: TORRE S17 1.70 M45 16/16
N: CAMPANA S21-S17 8/8 M45
O: TORRE S21 8/8 M45
P: TORRE S21 16/8 M45
X: CAMPANA C2322/21 16 /16 M45L /M45
T: TORRE S2322 16 /16 M45L
U: TORRE S2326 16 /16 M52 /M45L
Z: TORRE S2326 24 /16 M52

S75R24/26	S75R16/26	S75R16/22	S70R/16	S60R/16
H: 100,7m	H: 91,6 m	H: 81,5 m	H: 75,2 m	H: 69,3 m
P(t): 77.472	P(t): 76.351	P(t): 147	P(t): 58,6	P(t): 45
T(t): 27.523	T(t): 24.465	T(t): 20	T(t): 15,85	T(t): 11,9
M(t-m): 1906,22	M(t-m): 1486,24	M(t-m): 1144,3	M(t-m): 723,7	M(t-m): 510

Windzone A-B / DIN 15019



Mástil / Reacciones

Masts / Reactions

Maste / Eckdrücke


Mat / Réactions

Torre / Reazioni




Windzone A-B / DIN 15019
Bloque lastre de base
Base ballast block
Grundballastblöcke
Bloc de lest de base
Blocco di zavorra alla base

D : TORRE S/TL 50-52 1.20 M 39/M 39 8/8
E : TORRE TL 55 1.20 M 39/M 39 8/8
J : CAMPANA S17 10m 1.20/1.70 M 39/M 45 8/8



H(m): 50,6	H(m): 46,5	H(m): 40,7
4,5 x 4,5 m - 1,7 - HM 700	4,5 x 4,5 m - 1,2 / 1,7 - HB 700	3,8 x 3,8 m 1,2 HB 600
LASTRE: 121,6 Tn	LASTRE: 98,8 Tn	LASTRE: 72,6 Tn
R1= 95,6 Tn	R1= 79,2 Tn	R1= 66,15 Tn




H(m): 36,4	H(m): 28,6	H(m): 24,6
3,8 x 3,8 1,2 HB 600	3,8 x 3,8 1,2 HB 600	3,8 x 3,8 M 1,2 HB 600
LASTRE: 53 Tn	LASTRE: 53 Tn	LASTRE: 45,6 Tn
R1= 46,96 Tn	R1= 43,12 Tn	R1= 39,2 Tn

L(m) W(m) H(m) Peso(Kg)

Pluma tramo primero /


Jib heel section
Ausleger-Anlenkstück /
Pied de flèche
Settore articolato di braccio



1 11,85 1,04 1,32 982

Elemento intermedio de pluma


Intermediate jib section /
Ausleger-Zwischenstück
Elément interm. de flèche /
Spezzone di braccio



2	5,94	0,95	1,32	465
3	5,94	0,95	1,22	475
4	5,94	0,95	1,22	450
5	11,74	0,95	1,32	915
6	5,14	0,95	1,22	328
7	3,64	0,95	1,22	225
8	2,0	0,95	1,22	142

Contrapluma /


Counter-jib
Gegenausleger /
Contre-flèche
Controbraccio



11,5	0,26	1,48	1480
4,05	0,33	0,58	96

Elemento de torre /

Tower section
Turmstück /
Elément de mât
Elemento di torre



D	11,8	1,2	1,38	3017
D	8,0	1,2	1,38	2075
D	5,9	1,2	1,38	1560
D	4,0	1,2	1,38	1100
E	11,8	1,2	1,38	3782
E	8,0	1,2	1,38	2654
E	5,9	1,2	1,38	2090
E	4,0	1,2	1,38	1527
J	10	1,85	1,38	3520
K	11,8	1,85	1,85	4600
K	5,9	1,85	1,85	2472
K	3	1,85	1,85	1425
L	11,8	1,85	1,85	5520
M	11,8	1,85	1,85	5670
N	5,9	2,27	2,27	3500
O	11,8	2,27	2,27	5044
O	5,9	2,27	2,27	2640
O	3	2,27	2,27	1545
P	11,8	2,27	2,27	5700
X	6	2,27	2,29	4000
T	6	2,27	2,29	4300
U	6	2,31	2,34	5910
Z	6	2,61	2,34	5980

Bloque de contrapeso /


Counterweight blocks
Gegengewichtsblöcke /
Bloc de contrepoids
Blocco di contrappeso



A	2,94	0,30	1,25	2300
B	2,94	0,18	1,25	1400
C	1,70	0,18	1,25	850

Bloque lastre de base /

Base ballast block
Grundballastblöcke /
Bloc de lest de base
Blocco di zavorra alla base



4,4 1,2 0,3 3800

Gancho y Carro /

Hook and Trolley/Lasthaken - Laufkatze/
Crochet - Chariot /Gancio e Carrello



0,75	0,12	1,40	164
0,96	1,10	0,62	118

Cabeza de torre /

Tower head/Turmspitze /
Porte - flèche/Testa di torre






6,5 1,8 1,7 3504

Viga principal base /

Main base beam/
Hauptträger für fundamentkreuz
Poutre de châssis de base/
Trave principale della base



5,72 0,67 0,65 1560

		L(m)	W(m)	H(m)	Peso(Kg)
Semiviga secundaria base / Half base beam / Halbträger für fundamentkreuz semipoutre de châssis de base/ Semitrave secundaria della base		2,77	0,45	0,665	800
Elemento de empotre / Foundation anchor / Fundamentanker / Élément de scellement / El annegare.		S51 1,2 S52R 1,2 S60/8 1,85 S60R/16 1,85 S70/8 2,28 S70R/16 2,28 S75R16/22 (4x) 0,5 S75R16/26 (4x) 0,5 S75R24/26 (4x) 0,5	1,38 1,38 1,85 1,85 2,28 2,28 0,5 0,5 0,5	1,42 1,42 1,6 1,6 1,6 1,6 2,5 2,5 2,5	496 594 956 1108 1122 1274 710 790 850
		DIMA	2,31	2,34	0,8 1650

ESPECIFICACIONES SUJETAS A MODIFICACIONES SIN PREVIO AVISO.

Specifications subject to modification without notice.

Obiges kann ohne berstaendigung geaendert werden.

Specifications susceptibles de modification sans avis préalable.

Specifiche suscettibili di variazioni senza preavviso.

DECLINAMOS TODA RESPONSABILIDAD DERIVADA DE LA INFORMACION PROPORCIONADA.

This information is supplied without liability.

Sämtliche Angaben erfolgen ohne Gewähr.

Ces renseignements sont sans garantie.

Le indicazioni contenute si intendono salvo errori ed omissioni.