




SAEZ

CRANES



18 859 S 11^{8T}



	10	15	20	25	30	31,5	35	40	45	50	55	60	65	m	
65 m	4000	4000	4000	4000	4000	4000	3540	3030	2630	2310	2050	1830	1650	Kg	1
	10	15	16,8	20	25	30	35	40	45	50	55	60	65	m	2
	8000	8000	8000	6560	5070	4090	3390	2880	2480	2160	1900	1680	1500	Kg	3
60 m	10	15	20	25	30	35	38,8	40	45	50	55	60		m	1
	4000	4000	4000	4000	4000	4000	4000	3510	3050	2690	2400	2150		Kg	2
	10	15	19	20	25	30	35	40	45	50	55	60		m	3
	8000	8000	8000	7540	5850	4730	3940	3360	2900	2540	2250	2000		Kg	4
55 m	10	15	20	25	30	35	35,72	40	45	50	55			m	1
	4000	4000	4000	4000	4000	4000	4000	3860	3360	2970	2650			Kg	2
	10	15	20	20,6	25	30	35	40	45	50	55			m	3
	8000	8000	8000	8000	6420	5210	4350	3710	3210	2820	2500			Kg	4
50 m	10	15	20	25	30	35	40,73	40	45	50				m	1
	4000	4000	4000	4000	4000	4000	4000	4080	3560	3150				Kg	2
	10	15	20	21,6	25	30	35	40	45	50				m	3
	8000	8000	8000	8000	6780	5510	4610	3930	3410	3000				Kg	4
45 m	10	15	20	25	30	35	40	45						m	1
	4000	4000	4000	4000	4000	4000	4000	3650						Kg	2
	10	15	20	22	25	30	35	40	45					m	3
	8000	8000	8000	8000	6940	5640	4720	4030	3500					Kg	4
40 m	10	15	20	25	30	35	40							m	1
	4000	4000	4000	4000	4000	4000	4000							Kg	2
	10	15	20	22,8	25	30	35	40						m	3
	8000	8000	8000	8000	7210	5860	4910	4200						Kg	4
35 m	10	15	20	25	30	35								m	1
	4000	4000	4000	4000	4000	4000								Kg	2
	10	15	20	23,2	25	30	35							m	3
	8000	8000	8000	8000	7340	5970	5000							Kg	4

Curvas de cargas
Load diagrams
Lastkurven
Courbes de charges
Curve di carico

Bloque de contrapeso, Counterweight blocks, Gegengewichtsblöcke, Bloc de contrepoid, Blocco di contrappeso

	65 m			60 m			55 m			50 m		
	A	B	C	A	B	C	A	B	C	A	B	C
	8	-	-	8	-	-	7	1	-	6	2	-
	20000 Kg			20000 Kg			19000 Kg			18000 Kg		
	45 m			40 m			35 m			30 m		
	A	B	C	A	B	C	A	B	C	A	B	C
	6	1	-	6	-	-	4	2	-	3	2	-
	16500 Kg			15000 Kg			13000 Kg			10500 Kg		

Mecanismos, Mechanisms, Antriebe, Mécanismes, Meccanismi.

45 Hp (33Kw) - CC-5V

H.B.G 126Mts S/R Ø12

H.B.G LEBUS 320Mts S/R Ø12

		m/min	0 — 45.7	0 — 52	0 — 81	0 — 117	0 — 23.7	0 — 26	0 — 40	0 — 58
		Kg	4000	3000	2000	1250	8000	6000	4000	2500
		Kw	33	33	33	33	33	33	33	33

45 Hp (33Kw) - INV-5V

H.B.G 126Mts S/R Ø12

H.B.G LEBUS 320Mts S/R Ø12

		m/min	0 — 6.3	0 — 42	0 — 56	0 — 76.4	0 — 104	0 — 15	0 — 21	0 — 28	0 — 38	0 — 52
		Kg	4000	4000	3000	2000	1250	8000	8000	6000	4000	2500
		Kw	33	33	33	33	33	33	33	33	33	33

	m/min	11 / 37 / 75			11 / 37 / 75		
	Kw	3,0			3,0		
	r.p.m	0,3	0,6	0,9	0,3	0,6	0,9
	Nm	2 x 65			2 x 65		
	m/min	12 / 24			12 / 24		
	Kw	4 x 3			4 x 3		

	400 V 50 Hz	100m 4x35mm ²	GENERADOR 300 kVA	POTENCIA INSTALADA 60 KW
--	----------------	-----------------------------	----------------------	--------------------------------

	380 V 60 Hz	100m 4x35mm ²	OPCIONAL
--	----------------	-----------------------------	----------

- Elevación / Hoisting / Heben / Levage / Sollevamento
- Distribución / Trolleying / Katzfahren / Distribution / Diritubizione
- Orientación / Slewing / Schwenken / Orientation / Rotazione
- Traslacion / Travelling / Schienenfahren / Translation / Traslazione
- Cable / Rope / Seil / Câble / Fune

Windzone A-B / DIN 15019



Mástil / Reacciones

Masts / Reactions

Maste / Eckdrücke

Mat / Réactions

Torre / Reazioni



K = S 17 8/8
L = S 17 16/8
N = S 17-S 21 8/8
O = S 21 8/8
P = S 21 16/8

H (m)	42,8	36,9	31	25,1
M (T·m)	278,7	264,9	252,4	241,1
T (t)	8,8	7,9	7,0	6,1
P (t)	71,2	68,5	66,5	63,8
R ₁ (t)	113,6	107,8	102,4	97,8
R ₂ (t)	149,1	141,9	135,5	129,6

Windzone A-B / DIN 15019


Mástil / Reacciones

Masts / Reactions

Maste / Eckdrücke



Mat / Réactions

Torre / Reazioni




K = S17 8/8
L = S17 16/8
N = S17-S21 8/8
O = S21 8/8
P = S21 16/8


H (m)	54,6	51,7	48,7
M (T·m)	357,2	321,8	293,8
T (t)	10,6	10,1	9,7
P (t)	76,2	74,9	73,2
R ₁ (t)	151,4	135,0	120,3
R ₂ (t)	185,4	168,4	156,7



K = S17 8/8
L = S17 16/8
N = S21-S17 8/8
O = S21 8/8
P = S21 16/8




H (m)	66,4	63,5	60,5	57,6
M (T·m)	576,7	530,6	485,5	443,2
T (t)	13,3	12,7	12,2	11,8
P (t)	78,5	77,5	75,9	74,4
R ₁ (t)	192	175	159,1	144,1
R ₂ (t)	226,7	209,7	192,9	177,2




Windzone A-B / DIN 15019
Mástil / Reacciones
Masts / Reactions
Maste / Eckdrücke
Mat / Réactions
Torre / Reazioni

K = S17 8/8
L = S17 16/8
N = S21-S17 8/8
O = S21 8/8
P = S21 16/8
X = C2322/21 16/16 M45/M45L
T = S2322 16/16 M45L
U = S2326 16/16 M52/M45L
Z = S2326 24/16L M52




H (m)	96.7	92.5	86.5	80.5	74.5
M (T·m)	--	1267.6	1267.6	915.8	766.5
T (t)	--	22.9	22.9	18.6	13.5
P (t)	--	103.3	103.3	84.6	79.1
R1(t)	--	411.4	411.4	281	232.3
R2(t)	--	463.1	463.1	321.3	271.8

Windzone A-B / DIN 15019
Bloque lastre de base
Base ballast block
Grundballastblöcke
Bloc de lest de base
Blocco di zavorra alla base




4,5 x 4,5 m-1,7- HM 700

R1 (t)	73,6 t	74,4 t	75,6 t	78,8 t	80 t	81,3 t
H (m)	20,3 m	23,3 m	26,2 m	29,2 m	32,1 m	35,1 m
Z (t)	83,6 t	83,6 t	83,6 t	91,2 t	91,2 t	91,2 t
R1 (t)	82,4 t	86,7 t	88,1 t			
H (m)	38 m	41 m	43,9 m			
Z (t)	91,2 t	102,6 t	102,6t			



4,5 x 4,5 m-1,7- HM 700

R1 (t)	73,6 t	74,4 t	75,6 t	78,8 t	80 t	81,3 t
H (m)	20,1 m	23,1 m	26 m	29 m	31,9 m	34,9 m
Z (t)	83,6 t	83,6 t	83,6 t	91,2 t	91,2 t	91,2 t
R1 (t)	82,4 t	86,7 t	88,1 t			
H (m)	37,8 m	40,8 m	43,7 m			
Z (t)	91,2 t	102,6 t	102,6t			




4,5 x 4,5 m-1,7- HM 700

R1 (t)	73,6 t	74,4 t	75,6 t	78,8 t	80 t	81,3 t
H (m)	20,8 m	23,8 m	26,7 m	29,7 m	32,6 m	35,6 m
Z (t)	83,6 t	83,6 t	83,6 t	91,2 t	91,2 t	91,2 t
R1 (t)	82,4 t	86,7 t	88,1 t			
H (m)	38,5 m	41,5 m	44,4 m			
Z (t)	91,2 t	102,6 t	102,6t			

Windzone A-B / DIN 15019


Bloque lastre de base , Base ballast block, Grundballastblöck,
Bloc de lest de base, Blocco di zavorra alla base



4,5 x 4,5 m-1,7- HM 700

R1 (t)	73,6 t	74,4 t	75,6 t	78,8 t	80 t	81,3 t
H (m)	20 m	23 m	25,9 m	28,9 m	31,8 m	34,8 m
Z (t)	83,6 t	83,6 t	83,6 t	91,2 t	91,2 t	91,2 t


R1 (t)	82,4 t	86,7 t	88,1 t	94,4 t	95,3 t
H (m)	37,7 m	40,7 m	43,6 m	46,6 m	49,5 m
Z (t)	91,2 t	102,6 t	102,6 t	121,6 t	121,6 t



6 x 6 m-2,1/1,7- HB 900

R1 (t)	46,5 t	49,1 t	53,8 t	62,5 t	71,9 t
H (m)	26,2 m	32,1 m	38 m	41 m	44 m
Z (t)	53,2 t	53,2 t	53,2 t	53,2 t	57 t

R1 (t)	81,6 t	92,6 t	104,1 t	116,5 t
H (m)	47 m	50 m	53 m	56 m
Z (t)	68,4 t	76 t	87,4 t	95 t



6 x 6 m-2,1/1,7- HB 900

R1 (t)	46,5 t	49,1 t	53,8 t	62,5 t	71,9 t
H (m)	26,5 m	32,4 m	38,3 m	41,3 m	44,3 m
Z (t)	53,2 t	53,2 t	53,2 t	53,2 t	57 t

R1 (t)	81,6 t	92,6 t
H (m)	47,3 m	50,3 m
Z (t)	68,4 t	76 t

L(m) W(m) H(m) Peso(Kg)

Contrapluma /


Counter-jib /
Gegenausleger /
Contre-fleche /
Controbraccio



11,94 1,80 0,60 2575

Bloque de contrapeso /

Counterweight blocks /
Gegengewichtsblöcke /
Bloc de contrepoids /
Blocco di contrappeso




3,20 1,25 0,29 2500

1,83 1,25 0,29 1500

Base Cruciforme 4,5 X4,5 /


Crossbase 4,5 X 4,5 /
Fundamentkreuz 4,5 X 4,5 /
Châsis 4,5 X 4,5 /
Carro base 4,5 X 4,5



6,70 1,10 1,20 5750

Vigas auxil. de base /


Half base beams /
Halbträger für fundamentkreuz /
Semipoutre de châsis de base /
Travi di congiunzi di congiunzione



4,40 0,30 0,55 220

Bloque lastre de base /


Base ballast block /
Grundballastblöcke /
Bloc de lest de base
Blocco di zavorra alla base















4,40 0,30 1,20 3800





Bloque apoyo de base /

Base support block /
Grundballastblöcke /
Bloc de appui de base
Blocco di appoggio alla base



3,75 0,5 1,2 5400

		L(m)	W(m)	H(m)	Peso(Kg)		
Elemento de empotre / Foundation anchor / Fundamentanker / Élément de scellement El annegare Utillaje tramo de empotre Tool fixing anchors Vorrichtung fundamentanker Outillage de L'emént de scellement Ferramenta troncheto fondazione	       		1,85				
		S60/R16	1,85	1,85	1,6	1108	
		S70/8	2,27	2,27	1,6	1122	
		S70R/16	2,27	2,27	1,6	1274	
		S75R 8 /20	0.35	0.35	1.6	1200	
		S75R16/22	0.5	0.5	2.5	2840	
		S75R16/26	0.5	0.5	2.5	3160	
		S75R24/26	0.5	0.5	2.5	3400	
		Dima	2.31	2.34	0.8	1650	
Pluma tramo primero / Jib heel section / Ausleger-Anlenkstück / Pied de fleche / Settore articolato di braccio			11,90	1,25	2,30	5800	
Elemento intermedio de pluma / Intermediate jib section / Ausleger-Zwischenstück Élément interm. de fleche / Spezzone di braccio	    						
		N° 2					
		N° 3, N° 4, N° 5	2	11,60	1,13	2,25	2194
			3	11,60	1,13	1,80	1720
			4	5,30	1,13	1,80	620
			5	5,30	1,13	1,80	530
			6	5,30	1,13	1,80	470
			7	5,30	1,13	1,45	376
			8	5,30	1,13	1,45	326
			9	5,15	1,13	1,40	248
			11	5,15	1,13	2,25	1280
Gancho, Carro y Puntera / Hook, Trolley and jib head / Lasthaken - Laufkatze-Cabeça de Lança Crochet - Chariot-Pointe de fleche / Gancio - Carrello e Punta freccia	     						
			1,20	1,35	0,80	290	
			0,80	0,15	1,50	330	
			0,80	1,20	1,40	108	
Viga principal base 6x6 / Main base beam / Hauptträger für fundamentkreuz Poutre de châssis de base / Trave principale della base			8,65	0,78	0,92	4300	
Semiviga secundaria base 6x6 / Half base beam / Halbträger für fundamentkreuz Semipoutre de châssis de base / Semitrave secundaria della base			4,27	0,68	0,97	2025	

		L(m)	W(m)	H(m)	Peso(Kg)
Niveladores / Levellers / Spindel pyramide / Niveleurs / Piedi regolabile		1,20	1,20	0,90	250
		1,15	1,25	0,45	505
		1,15	0,25	0,45	450
Elemento de torre TL16 / Tower section TL16 / Turmstück TL16 / Element de mât TL16 / Elemento di torre TL16		K 11,8	1,85	1,85	4600
		K 5,9	1,85	1,85	2472
		K 3	1,85	1,85	1425
		L 11,8	1,85	1,85	5520
		O 11,8	2,27	2,27	5044
		O 5,9	2,27	2,27	2640
		O 3	2,27	2,27	1545
		P 11,8	2,27	2,27	5700
		N 5,9			3500
		X 6	2,27	2,29	4000
		T 6	2,27	2,29	4300
		U 6	2,31	2,34	5910
		Z 6	2,61	2,34	5980
Unidad de rotacion / Complete slewing unit / Drehbühne / Orientation / Rotazione		4,40	2,00	2,00	6600
Cabina y soporte / Cabin and support / Kabine und wartungs / Cabine et support / Cabina e supporto		3,00	1,15	2,35	558

ESPECIFICACIONES SUJETAS A MODIFICACIONES SIN PREVIO AVISO.

Specifications subject to modification without notice.

Obiges kann ohne berstaendigung geaendert werden.

Specifications susceptibles de modification sans avis préalable.

Specifiche suscettibili di variazioni senza preavviso.

DECLINAMOS TODA RESPONSABILIDAD DERIVADA DE LA INFORMACION PROPORCIONADA.

This information is supplied without liability.

Sämtliche Angaben erfolgen ohne Gewähr.

Ces renseignements sont sans garantie.

Le indicazioni contenute si intendono salvo errori ed omissioni.



UNE 58-101-92 FEM 1001-87
According to EC 98/37 instruction

Windzone A-B / DIN 15019

Viento max. fuerza de servicio 150km/h

Maximun wind speed out of service 150 km/h

Maximale windstärke, ohne Betrieb 150 km/h

Vent maximum, hors service 150 km/h

Vento max, fuori di servizio 150 km/h